

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-024156

(43)Date of publication of application : 26.01.2001

(51)Int.Cl.

H01L 27/04
H01L 21/822
H01L 21/8238
H01L 27/092

(21)Application number : 11-194338

(71)Applicant : FUJI ELECTRIC CO LTD

(22)Date of filing : 08.07.1999


(72)Inventor : YOSHIDA YUTAKA

(54) SEMICONDUCTOR INTEGRATED CIRCUIT

(57)Abstract:

PROBLEM TO BE SOLVED: To suppress the effect of noises on an analog circuit, and to measure even the leakage current of a circuit which consumes current under a steady state without increasing the number of terminals, in an IC with a digital circuit block, a clock oscillation block, a bias current-supply circuit block, an analog circuit block or the like.

SOLUTION: Well regions on an IC substrate of a digital circuit SYD such as blocks 1, 2 as noise sources and an analog circuit SYA such as blocks 4, 3 susceptible to noises are divided, and the power supplies and ground terminals of both systems are separated and both systems are separated in noises. A current is determined by supplying the blocks 2, 4, by which the current is made to flow under a steady state, with a bias current from the block 3. When potential difference among an analog power supply and ground terminals VDD-A, GND-A is eliminated, the supply of the bias current to the block 2 is stopped and the current of the block 2 reaches zero, and leakage currents in the digital power supply and ground terminals VDD-D, GND-D are measured.



LEGAL STATUS

[Date of request for examination]

11.09.2003

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision]

of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office